

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs 19, 20, 29, & 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4844-5)

-----

Set a basalt stone 15x8x8", 10" in the ground for cor. of secs. 19, 20, 29, & 30 mkd with 2 notches on S & 5 notches on E edges, from which

- A hemlock, 24" dia., bears N.54½°E., 62 lks., mkd: T27S R1W S20 BT.
- A cedar, 14" dia., bears S.31°E., 53 lks., mkd: T27S R1W S29 BT.
- A fir, 40" dia. bears S.34°W. 25 lks. mkd: T27S R1W S30 BT
- A fir, 40" dia. bears N.16°W. 66 lks. mkd: T27S R1W S19 BT

Thomas Shrum, Jr. - Wit. Bud Shrum - Feb 6, 1961 - C.S. 51/175

-----

Found - Stone marked as called for in GL0 notes.  
All trees have been destroyed.

Set - 16" D.Fir S.82°W., 84.3 ft.  
33" Cedar S.21°E., 110.5 ft.  
8" Hemlock N.43°E., 100.1 ft.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Nov. 1969 - C.S. File 54/94-50

-----

Found - 15x8x8 stone mkd. 2 notches south at cor.  
16" now 25" D.Fir, S.82°W., 84.3 ft. shows pitched over scribe marks.  
33" now 33" cedar S.21°E., 110.5 ft. scribe visible T27S R1W RE 1287 BT.  
10" Hemlock N.42°E., 98.7 ft. T27 & other marks over grown. Unrecorded  
No sign of S.89°E. BT  
Orig. 40" D.Fir now burnt stump, S.34°W., 16.5 ft. badly burnt, no face.

Set - Brass cap at sec. cor. mkd: COUNTY SURVEYORS T27S R1W  
OFFICE S 19|S 20  
1969 S 30|S 29

Reblazed & rescribed -  
10" Hemlock S.42°E., 98.7 ft. scribed CS BT.  
This corner falls in old cut unit. No other trees available.

Ronald A. Quimby, LS 1654 & Romanso E. Ware, LS 1005 - For: USFS - March 1980 - M79-32

-----

Found - Douglas Co. Surveyors Office brass cap on iron pipe.  
24" D.Fir bears S.82°W., 84.3 ft.  
continued next page

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor Secs 19, 20, 29, & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

33" Cedar bears S.21°E., 110.5 ft. with good scar.  
12" Hemlock bears N.43°E., 98.7 ft. (Rec. 100.1 ft.)  
New BTs- 6" D. Fir bears N.20° W., 12.7 ft. and scribed T27S  
R1W S19 BT  
Brass washer RLS #1005 in BT face. Set post and sign 4.0 ft.  
east of corner.