TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4847)

Set a basalt stone 14x8x8", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 36" dia., bears N.48°E., 27 lks., mkd: ¼ S20 BT.
A fir, 36" dia., bears S.32°W., 23 lks., mkd: ¼ S19 BT.

Thomas Shrum, Jr. - Wit. Bud Shrum - Feb 6, 1961 - C.S. 51/175

Found - Stone marked as called for in GLO notes.
36" D.Fir, N.32°W., 15.2 ft (S.32°W. in orig. notes)
36" D.Fir, S.48°E., 17.8 ft (N.48°E. in Orig. notes)
Set - 7" Hemlock, S.41°W., 55.7 ft.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Nov. 1969 - C.S. File 54/94-49

Found - 14x8x8" Stone mkd: ¼ on north face.,
36" D.Fir, now stump, N.32°W. 15.2 ft., opened for scribing, very rotten, but definite scribe marks.
36" D.Fir, now stump, S.48°E., 17.8 ft., shows good scar.
7", now 8" Hemlock, S.39°W. (Rec S.41°W.) 55.7 ft., scribe visible: ¼ S19 RE 1287 BT
Set - Brass Cap at Cor. Mkd: COUNTY SURVEYORS T27S R1W
OFFICE 1969 ¼ S 19|S 20
New BT - 8" Hemlock S.34°E. 51.5 ft. mks: ¼ S20 CS BT.

Fd Ok by J. Artman, 5/1990 - C.S. File 63/104-17
FD. Ok K. Hoffine, 7/1995 - M122-27