

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4849)

Set a basalt stone 20x6x6", 15" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

- A fir, 24" dia., bears S.85°E., 27 lks., mkd: ¼ S17 BT.
- A fir, 24" dia., bears S.71°W., 69 lks., mkd: ¼ S18 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Oct. 1969 - C.S. File 54/94-3

Found - Corner stone, firmly set at ¼ corner mkd: ¼

- 24" now 39" D.Fir S.71°W., 45.5 ft. shows good scar.
- 24" now 30" D.Fir S.85°E., 17.8 ft. shows good scar.

This tree broken top most of branches gone due to falling trees.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T27S R1W OFFICE 1969 ¼ S 18|S 17

New BT - 48" D.Fir N.61°E., scribed "¼ S17 CS BT". (No dist. given on corner renewal. 11/4/2008 JC DCSO)