

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor Secs 7, 8, 17, & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4849-50)

Set a basalt stone 24x15x15", 18" in the ground for cor. of secs. 7, 8, 17, & 18 mkd with 4 notches on S & 5 notches on E edges, from which

- A fir, 36" dia. bears N.23°E., 47 lks. mkd: T27S R1W S8 BT
- An Alder, 18" dia., bears S.46½°E., 97 lks., mkd: T27S R1W S17 BT.
- An Alder, 12" dia., bears S.60°W., 65 lks., mkd: T27S R1W S18 BT.
- A fir, 16" dia. bears N.31½°W. 67 lks. mkd: T27S R1W S7 BT

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Oct. 1969 - C.S. File 54/94-4

Found - Large stone at corner approx size but no marks found 36" now 47" D.Fir N.23°E., 31.0 ft. opened for scribe, fd. old axe work & parts of scribing badly burnt & rotten.
No trace of NW - SW or SE BTs. NW tree went down Little River. SW & SE BTs alders gone.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T27S R1W
OFFICE S 7 | S 8
1969 S 18 | S 17

- 6" W.Fir, N.2°E., 21.9 ft. scribed T27S R1W S8 CS BT
- 12" W.Fir N.16°W. 20.2 ft scribed T27S R1W S7 CS BT
- 6" D.Fir West 11.0 ft. scribed T27S R1W S18 CS BT
- 8" Cedar S.50°E., 93.5 ft scribed T27S R1W S17 CS BT

Fd. & used on BLM dependant resurvey by Jasper M. Sams & Donovan C. Harris, Cadastral Surveyors, under Group No. 747, surveyed June/Aug. 1971 - (DCSO records Vol 35 Pgs 14579-80)

Romanso Ware & Ronald Quimby - For: USFS - July 1980 - M79-48

Found - 1969 county brass cap
Found metal post & sign.
8" D.Fir west 11.0 ft. good scar.
18" hemlock N.16°W., 20.2 ft. good scar.
12" hemlock N.2°E., 21.9 ft. good scar.
48" D.Fir N.23°E., 31.0 ft. old face with cut.
8" cedar S.50°E., 93.5 ft. vis. scribes.

Set - Post & sign 5.0 ft. West.

continued next page

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Leonard Herzstein, USFS - Jim Landrum - 4/14/1982 - CS 61/32-5

Found - 1½" IP firmly set projecting 15" above ground with
brass cap properly mkd.
Orig. 54" D.Fir, N.23°E., 31.0 ft. with no marks
visible on previously opened blaze.
10" W.Fir (hemlock, M79-48) bears N.2°E., 21.9 ft.
with healed double blaze. 1969
8" R. cedar, downed S.50°E., 93.5 ft. with partial
healed double blaze face down, 1969
8" D.Fir, West, 11.0 ft. with healed double blaze.
16" W. fir, (hemlock, M79-48) bears N.16°W., 20.2
ft. with healed double blaze. 1969
Set - Added 3 ft. dia. mound of stone from which brass cap
and I.P. now project 6".
New BT - 10" R. cedar, S.65°E., 107.5 ft. scribed "T27S R1W
S17 CS BT".
Corner is about 100 ft. south of Little River on high flat
ground.

Fd. & used on M160-48 by T. Rambo, 3/2010

Michael J. Schwartz - Umpqua National Forest - June 2010 -
M161-14A&B

Found - The Brass Cap (properly mkd) and Iron Pipe set by
the County Surveyors Office in 1969, from which:
A 18" Hemlock snag, N.16°W., 20.2 ft., healed blaze
A 12" Hemlock snag, N.2°E., 219 ft., healed blaze
A 54" Fir, N.23°E., 31.0 ft., healed blaze
A W.Cedar, S.50°E., 93.5 ft., healed blaze
A 12" Fir, West, 11.0 ft., healed blaze