

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO recs Vol 11 Pg 4852)

Set a basalt stone 24x14x10", 18" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

A laurel, 14" dia., bears S.22°E., 17 lks., mkd: ¼ S8 BT.

A fir, 10" dia., bears S.1°W., 11 lks., mkd: ¼ S7 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Oct. 1969 - C.S. File 54/94

Not found. This also falls in old clear cut unit & burnt.

BLM dependent resurvey by Jasper M. Sams & Donovan C. Harris, Cadastral Surveyors, under Group No. 747, surveyed June/Aug. 1971 - (DCSO records Vol. 35 Page(s) 14580-1)

The ¼ sec. cor. of secs. 7 & 8, monumented with the orig. basalt stone, 36x20x12" firmly set, 30" in the ground mkd. ¼ on W face, from which the remaining orig. BT;

A fir stump, 19" dia., bears S.1°W., 11 lks. no marks visible.

At the corner point

Set an iron post, 28" long, 2½" dia., 16" in the ground, and in a mound of stone, 4 ft. base, to top with brass cap mkd:

T27S R1W

¼
S 7 | S 8

1971

No suitable BTs available within limits.

Deposit orig. stone alongside iron post.

Romanso Ware & Ronald Quimby - For: USFS - July 1980 - M79-48

Found - 2½" IP with 1971 BLM brass cap.

Orig. stump, 19" Fir S.1°W., 7.3 ft. no vis. marks.

New BTs- 6" Pine, N.7°W., 18.6 ft. "¼ S7 BT"

6" D.Fir, S.24°E., 14.8 ft. "¼ S8 BT"

Brass washer marked RLS 1005 set in BT faces.

Set - Post & sign 2.0 ft. East.

Michael Schwartz - Umpqua Nat'l Forest - 6/2010 - M161-14A&B

Found - Brass Cap (properly mkd) and Iron Pipe set by the BLM, from which

A 10" Pine, N.7°W., 18.6 ft., healed blaze.

A 10" Pine, S24°E., 14.8 ft., healed blaze.