

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor Secs 5, 6, 7 & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4852)

Set a basalt stone 12x12x6", 8" in the ground for cor of secs 5, 6, 7, & 8 mkd with 5 notches on S & E edges, from which

- A fir, 14" dia. bears N.12½°E. 52 lks. mkd: T27S R1W S5 BT
- A fir, 14" dia. bears S.77°E., 29 lks. mkd: T27S R1W S8 BT
- A fir, 16" dia. bears S.81°W., 10 lks. mkd: T27S R1W S7 BT
- A fir, 12" dia. bears N.25½°W. 83 lks. mkd: T27S R1W S6 BT

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Oct. 1969 - C.S. File 54/94-19

Found - 12x12x6 Stone, firmly in ground mkd. with correct notches.

- 14", now 26" D.Fir, N.12½°E 34.3 ft. shows good scar
- 14", now 26" D.Fir, S.77°E. 19.1 ft. shows good scar
- 16", now 28" D.Fir, S.81°W. 6.6 ft., shows good scar
- 12", now 39" D.Fir, N.25½°W. 54.8 ft shows good scar

Set - Brass Cap at Cor. mkd County Surveyors T27S R1W

Office	S 6 S 5
1969	S 7 S 8

All Bearing Trees OK and tagged.
This corner lies about 35 ft. west of ravine, course S.20°W.