

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6 only, (North)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GL0 survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4787)

Set a basalt stone 20x14x8 ins., 15" in ground for cor. of secs. 5, 6, 31 and 32, marked with 5 notches on E. and 1 notch on W. edges, from which

- A Fir 12" dia., bears N.80°E., 31 lks. dist. mkd. T26S R1W S32 BT.
- A Fir 36" dia., bears S.35°E., 34 lks. dist. mkd. T27S R1W S5 BT.
- A Cedar 36" dia., bears S.34°W., 52 lks. dist. mkd. T27S R1W S6 BT.
- A Fir 8" dia., bears N.72½°W., 37 lks. dist. mkd. T26S R1W S31 BT.

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4093 and 4102)

(Page 4093)
The cor. of secs. 5, 6, 31 and 32, which is a basalt stone 5x4x8 ins., above ground, firmly set, marked and witnessed as described by the surveyor general.

(Page 4102)
The old cor. of secs. 5, 6, 31 and 32, which I re-establish as the cor. of secs. 5 and 6, T27S R1W only, by obliterating marks on bearing trees referring to secs. 31 and 32.

Douglas Co. Surveyors Office - John M. Powell, and crew - Dec. 4, 1969 - C.S. File 54/94-72

Found - Corner stone, right size, but no marks.
36" now 40" Cedar S.28°W., (Rec. S.34°W.), scribe visible.
36" now 40" D.Fir S.35°W., 22.4 ft. shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office

T26S	R1W	S 31
T27S		S 6 S 5

1969

Bearing trees OK and tagged.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 13, 1970 - C.S. File 54/94-40

From Iron rod set as reference pins, see notes in file and 1969 renewal visit. This corner lies in center of road.
(Cont. Next Page)

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6 only, (North)

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

RESET corner to proper location. (sketch in file)
New BTs- 30" Cedar N.3°W., 34.3 ft. scribed T26S R1W S31 CS
BT.
12" Hemlock N.31°W., 49.6 ft. scribed T26S R1W S31
CS BT.