

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for 32 only *

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by S.C. Flint, Contract #473, dated June 5, 1883
-(DCSO records Vol. 11 Page(s) 4768)

Set post 40x4 ins. firmly in the ground for stan. ¼ sec. cor.
marked S C on N. and S. faces, from which
A Fir 26" dia., bears N.35°W., 102 lks. dist. mkd. S C ¼
S BT.
A Fir 5" dia., bears S.10°W., 29 lks. dist. mkd. S C ¼ S
BT.

GL0 survey by Homer D. Angell, Deputy Surveyor, under
Contract #746, dated May 5, 1902 - (DCSO records Vol. 11
Page(s) 4777)

(35.98 chs.)
Old ¼ sec. cor. on line which I destroy.
(40.00 chs.)
A Basalt stone 18x12x6 ins., 14" in the ground for stan. ¼
sec. cor. marked S C ¼ on N. face, from which
A Fir 18" dia., bears S.32°W., 15 lks. dist. mkd. S C ¼ S5
BT.
A Fir 16" dia., bears NW. 14 lks. dist. mkd. S C ¼ S32 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew -
Dec. 12, 1969 - C.S. File 54/94-86

Found - 18x12x6 stone, firmly in ground mkd. "¼" on N. face.
18" now 34" D.Fir S.32°W., 9.9 ft. opened for scribe
"¼".
16" D.Fir now snag, N.45°W., 9.2 ft., scribe
visible.
Set Brass cap at cor. mkd: County Surveyors Office
T 27 S R 1 W
¼ S 32
T 28 S
1969
New BTs- 30" D.Fir N.40°W., 22.5 ft. mkd. ¼ S32 CS BT.
28" D.Fir N.51°E., 21.7 ft. mkd. ¼ S32 CS BT.
I opened and destroyed scribing of SW. BT as this corner does
not refer to section 5.

* This is a common corner for S32/S5 per Fritz Ingram's GIS
calculations 4/93