

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 240340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ken Hoffine, LS #2291 - For: Lone Rock Timber - July 1995 - M 122-27

Set - 5/8"x40" IR with 2" alum. cap mkd: LONE ROCK TIMBER
T27S R1W C¹/₄ S20 1995 PLSS 2291
8" D.Fir, bears S.36°W., 22.7'. We scribe T27S R1W C¹/₄
S20 BT & tag tree.
8" D.Fir, bears N.76°W., 23.3'. We scribe T27S R1W C¹/₄
S20 BT & tag tree.
11" Hemlock bears S.61³/₄°E., 25.6'. We scribe T27S R1W
C¹/₄ S20 BT & tag tree.
9" Hemlock bears N.32°E., 18.9'. We scribe T27S R1W C¹/₄
S20 BT & tag tree.
Corner lies on gentle north slope.

Gerald Nygren - For: Seneca Jones Timber Co - 12/2015 - M170-40

Found - 2" Alum. cap & BT per M122-27
8" D.Fir, now 4' tall stump, bears S.36°W., 22.7',
healed face.
8" D.Fir, now 3.6' tall stump, bears N.76°W., 23.3',
healed face.
14" Hemlock, bears N.32°E., 18.9' visible scribe.
13" Hemlock, bears S.61°45'E., 25.6' visible scribe.
New BTs- 13" Hemlock, bears S.89°30'E. 35.4' scribed: C¹/₄ S20 BT
11" Hemlock, bears S.31°E., 24.4' scribed: C¹/₄ S20 BT
All new BTs established per this survey were measured to a
alum. nail with a ³/₄" brass washer marked "RLS 1035" in the
side center at the base of said trees. Bearings are to the
face of said trees to the nearest ¹/₄°.