

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4848)

-----

Set a fir post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S17 on N and 20 on S faces; from which  
A fir, 14" dia., bears N.62°E., 40 lks., mkd: ¼ S17 BT.  
A fir, 14" dia., bears S.6°W., 60 lks., mkd: ¼ S20 BT.

Thomas Shrum, Jr. - Wit. Bud Shrum - Feb 6, 1961 - C.S. 51/175

-----

Found - 14" D.Fir N.62°E., 26.4 ft. - rotten  
14" D.Fir S.6°W., 39.6 ft. - down.  
Set - ¾"x36" iron rod.  
12" D.Fir S.26½°W., 38.7 ft.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Dec. 1969 - C.S. File 54/94-66

-----

Found - No trace of iron rod at ¼ cor. but fd. squared stake 12" now 14" D.Fir S.26½°W., 38.7 ft. pitched over scribe visible.  
Orig. 14" D.Fir now burnt stump, N.62°E., 26.4 ft.  
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T27S R1W  
OFFICE ¼ S 17  
1969 S 20

B.O. - 3/4" iron rod N.40°E., 25.0 ft.  
This corner falls in clear cut unit about 490.00 ft. west of logging road. Marker on road.

Ronald Quimby LS 1654, BHW Eng. - For: USFS - April 1980 - C.S. File 58/229-1

-----

Found - 1969 County Brass cap on iron pipe.  
A 16" Fir, S.26.5°W., 38.7 ft. good scar.  
New BT - We scribed a 6" Fir, N.59°E., 12.2 ft. scribed ¼ S17 BT with brass washer in BT face RLS 1005.

FD. Ok K. Hoffine, 7/1995 - M122-27