

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4850)

Set a basalt stone 15x10x8", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

- A maple, 12" dia., bears N.63°E., 50 lks., mkd: ¼ S8 BT.
- A fir, 30" dia., bears S.20°W., 43 lks., mkd: ¼ S17 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Oct. 1969 & 4/13/1970 - C.S. File 54/94-105

Reported as not found
10/1969
Found old E-W blazed line. Area to the north mostly clear cut. Area to the South partial cut.
Also burnt - trees out very low to ground probably all traces gone.
4/13/1970
BTs 1 fir - 1 maple
Found E-W line old brushing & ribbon - this cor. lies in a old partial cut. May here been taken by old rd. or possibly burnt.

BLM dependent resurvey by Jasper M. Sams & Donovan C. Harris, Cadastral Surveyors, under Group No. 747, surveyed June/Aug. 1971 - (DCSO records Vol. 35 Page(s) 14579)

The sec. cor. of secs. 8 and 17, monumented with a broken basalt stone, 10x10x5", firmly set, protruding 4" above the ground, no marks visible; from which the remains of the original bearing trees:

- A root wad of a maple, size indeterminate, bears N.63°E., 50 lks., no remains of tree.
- A fir snag, 43" dia., bears S.20°W., 43 lks., with burned and rotted blaze and good axe marks at top and bottom of face, no scribe marks remaining.

At the corner point
Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap marked:

	T27S R1W
¼	$\frac{S \ 8}{S \ 17}$
	1971

from which

- A cedar, 33" dia., bears S.69°W., 110 lks., mkd: ¼ S17 BT.
- A fir, 50" dia., bears N.9°W., 74 lks., mkd: ¼ S8 BT.

Deposit the basalt stone alongside iron post.

cont.

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Romanso Ware & Ronald Quimby - For: USFS - July 1980 - M79-48

Found - 1971 BLM brass cap properly marked.
54" Fir, N.4°E., 50.3 ft. vis. scribes
Metal Post and sign 4.0 ft. West.
New BT - 8" Fir, S.25°W., 34.3 ft. "¼ S17 BT".
Brass washer marked RLS 1005 set in BT face.

Fd. & used on M160-48 by T. Rambo, 3/2010

Michael J. Schwartz - Umpqua National Forest - June 2010 -
M161-14A&B

Found - The BLM Iron Pipe and brass cap (properly mkd), from
which:
A 14" Fir, S.21¼°W., 32.4 ft., healed blaze
A 54" Fir, N.9½°W., 48.6 ft., healed blaze