

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4853)

-----

Set a basalt stone 12x10x6", 8" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which  
A fir, 14" dia., bears S.13°E., 12 lks., mkd: ¼ S8 BT.  
A fir, 20" dia., bears N.30°W., 44 lks., mkd: ¼ S5 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Oct. 1969 - C.S. File 54/94-20

-----

Found - Stone, out of ground, down hill 3 ft. from corner mkd. ¼  
14" now 30" D.Fir S.13°E., 7.9 ft. shows good scar.  
20" now 38" D.Fir N.9°E., (Rec. N.30°W.) 29.0 ft. open for scribe.

Set - By using 2 distances & 1 bearing brass cap at cor. mkd:  
COUNTY SURVEYORS T27S R1W  
OFFICE ¼ S 5  
1969 S 8

Reblazed & rescribed -  
38" D.Fir N.9°E., 29.0 ft. scribed "¼ S5 CS BT"  
30" D.Fir S.13°E., 7.9 ft. scribed "¼ S8 CS BT"

Romanso Ware & Ronald Quimby - For: USFS - July 1980 - M79-48

-----

Found - 1½" IP with brass cap (properly) marked.  
32" Fir, S.8°W., 7.9 ft. vis. scribes.  
36" Fir, N.9°E., 29.0 ft. vis. scribes.

Set - Post & sign 5.0 ft. North.