

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747 dated May 5 1902 - (DCSO rec Vol 11 Pgs 4832-3)

-----  
Set a basalt stone 12x10x8", 8" in the ground for cor. of secs. 28, 29, 32, & 33 mkd with 1 notch on S & 4 notches on E edges, from which

- A cedar, 18" dia., bears N.32°E., 37 lks., mkd: T27S R1W S28 BT.
- A cedar, 30" dia., bears S.40°E., 67 lks., mkd: T27S R1W S33 BT.
- A hemlock, 12" dia., bears S.30°W., 50 lks., mkd: T27S R1W S32 BT.
- A hemlock, 10" dia., bears N.71°W., 15 lks., mkd: T27S R1W S29 BT.

Pg 4833 Line tree bet. Secs. 28 & 33 bears S.89°52'E 0.05 chs

-----  
Douglas Co. Surveyors Office - L.E. Monrean - P.L. Earle - A.V. Cangie - 6/19/1975 - C.S. File 57/30-11

-----  
Found - 12x10x8" basalt stone on surface of ground. 4 notches on east edge & 1 notch on south edge.

63" dia., . fir stump bears N.78°E, 8½ ft. Stump cut below normal notch height. Orig. notes call for 60" fir on line between secs. 28 & 33 a dist. of 3.3 ft. east of corner.

No bearing trees fd. Orig. call on south line to spring checked, no trace of cabin, area cat logged & burned.

Renewal: 3.3 ft. West of line tree.

Set - Iron pipe 2½ ft. in length 1½" in dia. with 2½" brass cap stamped: COUNTY SURVEYORS OFFICE 1975

T27S	R1W
S 29	S 28
S 32	S 33

Bearing objects (no trees available) -

5/8" IR with alum. cap 1½" dia., center punched & stamped "DOUGLAS CO. SURVEYOR B.O. No. 1" set in orig. line tree stump bears N.75°E., 3.8 ft.

5/8" IR with alum. cap 1½" in dia., set in 48" dia., cedar stump bears S.25½°E., 64.4 ft. cap center punched & stamped DOUGLAS CO SURVEYOR B.O. No. 2

5/8" iron rod with alum. cap 1½" in dia., cap center punched & stamped "DOUGLAS CO. SURVEYOR" B.O. No. 3 BEARS S.75°W., 22.2 ft.

12x10x8" stone (Basalt) with 4 notches on east edge & one notch on south edge, lying on ground surface. Bears S.59°W., 5.8 ft.

continued next page

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>5/8 " Iron rod with alum cap 1½" in dia set in a 30" dia. fir stump. Cap center punched &amp; stamped DOUGLAS CO SURVEYOR BO NO.4 bears N.58½°W 70.8 ft</p>
<p>Ronald A. Quimby, RLS 1654 &amp; Romanso E. Ware, RLS 1005 - For: US Forest Service - March 1980 - M79-32</p> <p>-----</p> <p>Found - 1½" Iron pipe with brass cap. Bearing object #1 5/8" Iron Rod and alum, cap in stump bears N.75°E., 3.8 ft. Bearing object #2 5/8" Iron Rod and alum, cap in 48" cedar stump bears S.26°E., 64.4 ft. Bearing object #3 5/8" Iron rod and alum, cap bears S.75°W., 22.2 ft. Bearing object #4 5/8" Iron Rod and alum, cap in 30" Fir stump bears N.59°W., 70.8 ft.</p> <p>New - Set post and signs 3.0 feet west of corner.</p>
<p>2</p>