

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4834)

Set a basalt stone 12x10x8", 8" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A hemlock, 12" dia., bears N.79°E., 22 lks., mkd: ¼ S28 BT
A hemlock, 18" dia., bears S.2°W., 32 lks., mkd: ¼ S29 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Nov. 1969 - C.S. File 54/94

Reported as not found.
This cor falls in logged unit 1 chain from a draw. 2 small hemlocks not found.

Ronald A. Quimby, RLS 1654 & Romanso E. Ware, RLS 1005 - For: US Forest Service - March 1980 - M79-32

Set - 2½" Iron pipe with brass cap.
BTs- 6" D.Fir bears S.75°E., 14.8 ft. scribed "¼ S28 BT".
14" D.Fir bears N.31°W., 65.0 ft. scribed "¼ S29 BT".
Set post and sign 3.0 ft. east of corner. Both trees have brass washers - RLS 1005 - in B.T. face.