

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4834)

-----

Set a basalt stone 15x12x4", 10" in the ground for cor. of secs. 20, 21, 28, & 29 mkd with 2 notches on S & 4 notches on E edges, from which

- A fir, 24" dia., bears N.29°E., 107 lks., mkd: T27S R1W S21 BT.
- A fir, 36" dia. bears S.60°E. 80 lks. mkd: T27S R1W S28 BT
- A pine, 30" dia., bears S.86°W., 37 lks., mkd: T27S R1W S29 BT.
- A fir, 14" dia., bears N.34°W., 100 lks., mkd: T27S R1W S20 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Nov. 1969 - C.S. File 54/94-47

-----

Found - 15x12x4 stone, very loose in ground, notches on correct sides.

- 14" D.Fir, now stob, N.34°W., 66.0 ft. prev. opened "T27 R" visible.
- 36" D.Fir now down, S.60°E., 52.8 ft. scribe visible "T27S R1W S28"
- 24" Fir, now burnt stump, N.29°E., 70.6 ft.

No trace of SW BT

Set - Brass cap at sec. cor. mkd: COUNTY SURVEYORS T27S R1W  
OFFICE S 20 | S 21  
1969 S 29 | S 28

New BTs- 4" D.Fir N.9°E., 23.0 ft. mkd: S21 CS BT  
6" D.Fir N.59½°E., 9.4 ft. mkd: T27S R1W S21 CS BT  
6" Maple S.3°E., 15.7 ft. mkd: T27S R1W S28 CS BT  
7" Maple S.61°W., 20.1 ft. mkd: T27S R1W S29 CS BT

Douglas Co. Surveyors Office - Randall Smith - Stephen Clause - June 29, 1988 - C.S. File 62/52-7

-----

Found - Orig. 15x12x4" stone with 2 notches on a side, and 4 notches on another side found laying flat on top of ground loose and apparently out of position. (Corner position as determined by BTs is 2 ft. southerly from found position of stone.)

DCSO BC/IP set 1969 Ren. is gone.

- 14" now 20" dia. 10 ft. high D.Fir stob with a previously opened blaze and scribing visible "T27S" bears N.34°W. 66.0 ft (agrees w/rec.) Orig

continued next page

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28, & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

36" now 42" dia. down D.Fir with a previously opened blaze, illegible scribing visible, bears S.60°E., 52.8 ft. to root hole. (agrees with record) Orig.  
24" now 30" dia. 1½ ft. high burnt D.Fir stump, no blazes or scribing visible, bears N.29°E., 70.6 ft. (agrees with record) Original  
30" Pine now 30" dia. 1½ ft. high rotted tipped out stump (unable to identify species) bears S.86°W., 24.4 ft. to root hole. (agrees with orig. record)  
4" now 12" dia. D. fir with a fully healed double blaze, bears N.7½°E., 22.6 ft. (Rec. N.9°E., 23.0 ft. dist. to center of trunk.) 1969  
6" now 12" dia. D. fir with a fully healed double blaze, bears N.59½°E., 9.4 ft. (agrees with rec.)  
6" now 8" dia. maple with a partially healed single blaze scribing visible "R1W 328' bears S.3°E., 16.1 ft. (Rec. S.3°E., 15.7 ft. is to center of trunk.) 1969  
7" now 11" dia. Maple with a partially healed double blaze, scribing visible "1W S29 CS BT" bears S.61°W., 20.4 ft. (Rec. S.61°W., 20.1 ft. dist. to center of trunk.) 1969  
Set - Corner position determined from orig. and 1969 bearing trees. A DCS0 brass cap on a 1¼" O.D. x 32" long I.P. is set and protrudes 6" above ground. The original corner stone is set along south edge of BC/IP with 2 notches on south and 4 notches on east edge, top of stone protrudes 6" above ground and measures 9" x 3" wide. A 2½ ft. dia. mound of stone surrounds corner. Cap is mkd. "Douglas County Surveyor T27S S20 S21 S29 S28 R1W 1988".  
No new accessories. Corner is approx. 60 ft. north of Forest service Rd.# 2792-086.

Gerald Nygren - For: Seneca Jones Timber Co - 12/2015 - M170-40  
-----  
Found - 1988 Co. Surveyor brass cap & BT per rec.  
24" D.Fir, now 9' tall snag, bears N.34°W., 66.0', visible scribe.  
24" D.Fir, bears N.59°30'E., 9.4' healed face.  
9" Maple, bears S.03°E., 16.1' healed face.  
12" Maple, bears S.61°W., 20.4' healed face.  
21" D.Fir, bears N.07°30'E., 22.6' healed face.