

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4836)</p> <p>-----</p> <p>Set a basalt stone 15x10x8", 10" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which A hemlock, 20" dia., bears N.34°E., 46 lks., mkd: ¼ S21 BT A fir, 12" dia., bears S.65°W., 35 lks., mkd: ¼ S20 BT.</p>
<p>Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Dec. 1969 - C.S. File 54/94-68</p> <p>-----</p> <p>Found - No trace of corner stone 20" now 30" Hemlock N.34°E., 30.4 ft scribe visible. "¼" "2" "T" 12" Fir, now down, S.65°W., 23.1 ft., opened for scribe "¼ S20 BT"</p> <p>Set - Brass cap at cor. mkd: COUNTY SURVEYORS T27S R1W OFFICE 1969 ¼ S 20 S 21</p> <p>New BT - 42" D.Fir N.57°W., 39.2 ft. scribed ¼ S20 CS BT</p>
<p>Gerald V. Nygren - For: USFS - March 1988 - C.S. 63/69-7</p> <p>-----</p> <p>Found - A 1" iron pipe with 2¼" brass cap extending 6" above ground set by Douglas County Surveyor stamped "T27S R1W ¼ S20 S21 1969" A 30" Hemlock stump, bears N.35°E., 30.5 ft. (vis. scar) 42" fir stump, bears N.54½°W, 39.7 ft. (vis. scribe) 14" Hemlock, bears S.28¾°E, 69.1 ft. (vis. scribe)</p> <p>New BT - A 8" D.Fir, bears S.01°W, 32.4 ft., scribed "¼ S20 BT" with a 1/2" brass washer marked "RLS 1035" nailed flush to lower end of blaze</p>
<p>Fd. Ok by K. Hoffine - 7/1995 - M122-27</p>
<p>Gerald Nygren - For: Seneca Jones Timber Co - 12/2015 - M170-40</p> <p>-----</p> <p>Found - 1969 Co. Surveyor brass cap & BTs per rec. 14" Hemlock, now 9' tall stump, bears S.28°45'E., 69.1', healed face. 30" Hemlock stump, bears N.35°E., 30.5' healed face. 42" D.Fir stump, bears N.54°30'. , 39.7' visible scribe. 17" D., Fir, bears S.01°W., 32.4' healed face.</p> <p>New BTs- 17" D.Fir, bears N.64°45'W., 32.7' scribed: ¼ S20 BT 14" D.Fir, bears S.82°45'W., 31.7' scribed: ¼ S20 BT 22" D.Fir, bears N.83°E., 54.7' scribed: ¼ S21 BT</p> <p>continued next page</p>

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

All new BTs established per this survey were measured to a alum. nail with a $\frac{3}{4}$ " brass washer marked "RLS 1035" in the side center at the base of said trees. Bearings are to the face of said trees to the nearest $\frac{1}{4}$ °.