

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor. Secs 16, 17, 20, & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4836)

Set a basalt stone 15x12x8", 10" in the ground for cor. of secs. 16, 17, 20, & 21 mkd with 3 notches on S & 4 notches on E edges, from which

- A cedar, 14" dia., bears N.71°E., 39 lks., mkd: T27S R1W S16 BT.
- A hemlock, 28" dia., bears S.70°E., 50 lks., mkd: T27S R1W S21 BT.
- A cedar, 30" dia., bears S.65°W., 60 lks., mkd: T27S R1W S20 BT.
- A hemlock, 30" dia., bears N.48°W., 28 lks., mkd: T27S R1W S17 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Dec. 1969 - C.S. File 54/94-67

Found - 15x12x8" Stone, firmly set, 4 notches on East Side.
14", now 24" Cedar, N.71°E. 25.7 ft. has rotted face
30", now 38" Cedar, S.65°W. 39.6 ft. has rotted face
28" now 35" Hemlock S.70°E. 33.0 ft. scribe visible,
"T"
30" now 40" Hemlock, N.48°W. 18.5 ft. scribe visible. "W"

Set - Brass Cap at Cor. mkd: COUNTY SURVEYORS T27S R1W
Office S 17 | S 16
1969 S 20 | S 21

New BTs- 13 Hemlock S.38°E. 19.0 ft. mkd: T27S R1W S21 CS BT
30" Hemlock N.19°E. 30.3 ft. mkd: T27S R1W S16 CS BT
8" Hemlock S.76½°W. 35.5 ft. mkd: T27S R1W S20 CS BT