

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4838)

Set a basalt stone 15x12x4", 10" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

- A fir, 18" dia., bears S.68°E., 26 lks., mkd: ¼ S16 BT.
- A fir, 20" dia., bears S.60°W., 33 lks., mkd: ¼ S17 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Dec. 1969 - C.S. File 54/94-76

Found - No trace of Corner Stone.
No trace of SE BT (Skid Road)
20", now 31" D.Fir, Snag Top, S.60°W. 21.8 ft.,
opened for scribing. "¼ S1"

Set - Brass Cap at Cor. mkd: COUNTY SURVEYORS T27S R1W
OFFICE 1969 ¼ S 17 | S 16

New BTs- 19" D.Fir S.1°E. 40.0 ft. mkd: "¼ S16 CS BT".
33" D.Fir S.52°W. 37.4 ft. mkd: "¼ S17 CS BT".