

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO rec Vol. 11 Pg 4838)

Set a basalt stone 18x10x8", 14" in the ground for cor. of secs. 8, 9, 16, & 17 mkd with 4 notches on S & E edges, from which

- A fir, 30" dia. bears N.80°E. 30 lks. mkd: T27S R1W S9 BT
- A hemlock, 12" dia., bears S.19½°E., 49 lks., mkd: T27S R1W S16 BT.
- A fir, 12" dia., bears S.19½°W., 49 lks., mkd: T27S R1W S17 BT.
- A fir, 30" dia., bears NW., 21 lks., mkd: T27S R1W S8 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Dec. 1969 - C.S. File 54/94

Reported as not found.
Found good N-S blazed line. Also 1945 forest location tag had good call on spring branch approx. 25.0 South of cor. Not real good info on corner also a lot of blow down -good not get anything to jibe up.

BLM dependent resurvey by Jasper M. Sams & Donovan C. Harris, Cadastral Surveyors, under Group No. 747, surveyed June/Aug. 1971 - (DCSO records Vol. 35 Page(s) 14575)

The cor. of secs. 8, 9, 16 & 17, determined from the remaining orig. BTs:

- A hemlock 26" dia., bears S.16½°E., 44 lks., with a downed fir, 40" dia., lying in front of the face, (slope dist. to tree is 49 lks. (Rec. S.19½°E., 49 lks.)
- A fir snag 42" dia., bears N.45°W., 21 lks., mkd: T27S R1W S8 BT, on opened blaze, and metal location tag on tree dated 9/27/43.

At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T27S	R1W
S 8	S 9
S 17	S 16
1971	

from which

- A fir, 49" dia., bears N.8°E., 11 lks. mkd: T27S R1W S9 BT
- A fir, 38" dia. bears S.78°E. 26 lks. mkd: T27S R1W S16 BT
- A fir, 31" dia., bears S.78°W., 113 lks., mkd: T27S R1W S17 BT.
- A hemlock, 12" dia., bears N.70°W., 162 lks., mkd: T27S R1W S8 BT.

cont. next pg

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Romanso E. Ware & Ronald Quimby - For: USFS - 7/1980 - M79-48

Found - 1971 BLM brass cap properly marked.
50" Fir N.8°E., 7.3 ft. vis. scribes.
38" Fir S.70°E., 17.2 ft.
12" Hemlock S.12°W., 40 ft.
32" Fir, S.76°W., 74.6 ft.
26" Hemlock S.16½°E., 29.0 ft. (Orig. Tree)
Down 40" Fir S.19½°E., 32.3 ft. (Orig. Tree)
42" Fir snag N.45°W., 13.9 ft. (Orig. Tree)
Set - Post & sign 1.0' south

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - John Powell - June 7, 1982 - C.S. File 61/36-22

Found - 1971 BLM brass cap on 2½" I.P. protruding 4" out of ground on very steep, logged over slope. Cap is a standard BLM cap properly marked.
49" fir per resurvey, now 50" stump which has been split open with scribed "BT" visible in previously opened face bears N.8°E 7.3 ft. (as per record)
38" fir per resurvey, now 38" stump with scribed "R1W" visible in previously opened face bears S.78°E., 17.2 ft. (as per rec.)
12" hemlock per resurvey, now 12" stump with scribed "T27S R1W S8 BT" visible in unhealed blaze bears N.73°W., 109.8 ft. (Rec. per resurvey N.70°W., 106.9 ft.)
New - Set spike in top of 26" hemlock stump, stamped "B01" bears S.14°W., 29.9 ft.
Set spike, stamped "B02" in top of 46" fir stump bears N.81°W., 97.7 ft.
Sketch in C.S. file.