

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4839)

Set a basalt stone 12x10x6", 8" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A fir, 14" dia., bears N.33°E., 29 lks., mkd: ¼ S9 BT.
A cedar, 12" dia., bears S.32½°W., 58 lks., mkd: ¼ S8 BT.

BLM dependent resurvey by Jasper M. Sams & Donovan C. Harris, Cadastral Surveyors, under Group No. 747, surveyed June/Aug. 1971 - (DCSO records Vol. 35 Page(s) 14576)

The ¼ sec. cor. of secs. 8 & 9, monumented with the original basalt stone 11x10x6" firmly set, 10" in the ground with fragmentary chisel marks visible on W face, from which the orig. bearing trees:
A fir, 17" dia., bears N.4½°E., 30 lks., mkd. with healed blaze & old metal location tag. (Rec. N.33°E., 29 lks.)
A cedar, 18" dia., bears S.4°W., 60 lks., with fragmentary scribe marks visible on partially healed blaze. (Rec. S.32½°W., 58 lks)
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:
T27S R1W
¼
S 8|S 9
1971
Deposit orig. stone alongside iron post.

Romanso E. Ware & Ronald Quimby - For: USFS - 7/1980 - M79-48

Found - 1971 BLM brass cap properly marked.
17" D.Fir N.4½°E., 19.8 ft.
18" Cedar, S.4°W., 39.6 ft.
Set - Post & sign 4 ft. North.