

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs 4, 5, 8, & 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4839-40)

-----

Set a basalt stone 15x12x5", 10" in the ground for cor. of secs. 4, 5, 8, & 9 mkd with 5 notches on S & 4 notches on E edges, from which

- A fir, 16" dia. bears N.46°E., 59 lks. mkd: T27S R1W S4 BT
- A fir, 30" dia. bears S.27°E., 58 lks. mkd: T27S R1W S9 BT
- A cedar, 16" dia., bears S.82°W., 73 lks., mkd: T27S R1W S8 BT.
- A cedar, 14" dia., bears N.85½°W., 62 lks., mkd: T27S R1W S5 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Oct. 1969 - C.S. File 54/94-21

-----

Found - 15x12x5" stone firmly set at sec. cor. mkd. with notches.

- 16" now 32" D.Fir N.46°E., 37.0 ft. shows good scar.
- 30" D.Fir now stob S.27°E., 36.3 ft. scribe visible  
T27S R1W S9 BT
- 16" cedar now 36" S.82°W., 48.2 ft. shows good scar.
- 14" now 21" Cedar, N.85½°W., 40.9 ft. burnt face scribe visible "27"

Set - Brass cap at sec. cor. mkd: COUNTY SURVEYORS T27S R1W  
OFFICE S 5 | S 4  
1969 S 8 | S 9

New BT - 30" D.Fir S.5°E., 28.1 ft. mkd: T27S R1W S9 CS BT  
Reblazed & rescribed -  
21" Cedar N.85½°W., 40.9 ft. mkd: T27S R1W S5 CS BT.