

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5 only, (North)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4788)

Set a basalt stone 15x12x5 ins., 10" in ground for cor. of secs. 4, 5, 32 and 33, marked with 4 notches on E. and 2 notches on W. faces, from which
A Hemlock 10" dia., bears N.53°E., 38 lks. dist. mkd. T26S R1W S33 BT.
A Hemlock 12" dia., bears S.44°E., 78 lks. dist. mkd. T27S R1W S4 BT.
A Hemlock 24" dia., bears S.67°W., 49 lks. dist. mkd. T27S R1W S5 BT.
A Hemlock 14" dia., bears N.52°W., 55 lks. dist. mkd. T26S R1W S32 BT.

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4093 and 4101)

(Page 4093)
The cor. of secs. 4, 5, 32 and 33, which is a basalt stone 5x12x5 ins., above ground, firmly set, marked and witnessed as described by the surveyor general.
(Page 4101)
The old cor. of secs. 4, 5, 32 and 33, which I re-establish as the cor. of secs. 4 and 5, T27S R1W only, by obliterating marks on bearing trees referring to secs. 32 and 33.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 5, 1969 - C.S. File 54/94-29

Found - No trace of Corner stone nor SW. BT.
12" Hemlock now snag, S.44°E., 51.5 ft., scribe visible.
Set Brass cap at cor. mkd: County Surveyors Office
T26S R1W S 32
T27S 1969 S 5 | S 4
New BTs- 15" Hemlock S.24°W., 40.1 ft. mkd. T27S R1W S5 CS BT
13" Cedar S.28°E., 53.2 ft. mkd. T27S R1W S4 CS BT.