

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 301100

PRIMARY CORNER DESCRIPTION C C for Secs. 4 & 5 only, T28-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5409)

Set a basalt stone 12x8x8 ins., 8" in the ground for closing cor. of secs. 4 and 5, marked with C C on S. and 4 notches on E. and 2 notches on W. edges; from which
A Fir 14" dia., bears S.15°E., 39 lks. dist. mkd. T28S R1W S4 BT.
A Fir 12" dia., bears SW. 68 lks. dist. mkd. T28S R1W S5 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Jan. 9, 1070 - C.S. File 54/94-2

Found - 12x8x8 corner stone in place and mkd. 4 notches E. and 2 on W. plus two good BTs.
14" D.Fir now 26", S.15°E., 25.7 ft., shows good axe face.
12" D.Fir now 20", S.45°W., 44.9 ft., opened and found scribing of "BT".

Set Brass cap at cor. mkd: County Surveyors Office
T27S R1W CC S 33
T28S 1970 S 5 | S 4

No new BTs needed. This C C of 4 & 5 lies 10.4 ft. East of the sec. cor. of 32 & 33, T27-1.