

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 33 only

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by S.C. Flint, Contract #473, dated June 5, 1883
-(DCSO records Vol. 11 Page(s) 4768-69)

Set post 44x4 ins., firmly in the ground for stan. ¼ sec.
cor. marked S C on N. and S. faces, from which
 A Fir 10" dia., bears S.60°W., 10 lks. dist. mkd. S C ¼ S
 BT.
 A Fir 9" dia., bears N.60°W., 9 lks. dist. mkd. S C ¼ S
 BT.

GLO survey by Homer D. Angell, Deputy Surveyor, under
Contract #746, dated May 5, 1902 - (DCSO records Vol. 11
Page(s) 4776)

(36.45 chs.)
Old ¼ sec. cor. on line which I destroy.
(40.00 chs.)
Set Hemlock stake 3 ft. long, and 3' sq., 24" in the ground
for stan. ¼ sec.cor. marked S C ¼ S33 on N. face and 4 on S.
face, from which
 A Fir 10" dia., bears N.62°E., 21 lks. dist. mkd. S C ¼
 S33 BT.
 A Fir 12" dia., bears S.40°E., 18 lks. dist. mkd. S C ¼ S3
 BT.

Douglas Co. Surveyors Office - Crew - 1/9/70 - C.S. File
54/94

Not Found.
We had good line and good calls and we found ¼ that was
destroyed, which was at 36 chs. approx. and new 40 chs. we
found no trace of new cor. or BTs.