

PRIMARY CORNER DESCRIPTION 1/4 Cor. 16 & 21

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4837)

-----

Set a basalt stone 12x8x6", 8" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

- A fir, 40" dia., bears North, 12 lks., mkd: ¼ S16 BT.
- A fir, 30" dia., bears S.50°W., 47 lks., mkd: ¼ S21 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Nov. 1969 - C.S. File 54/94-60

-----

Found - No trace of corner stone.  
40" now 48" D.Fir North 7.9 ft. tree opened at earlier time, "16" visible  
30" now 40" D.Fir S.50°W., 31.0 ft. shows good scar.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T27S S 16  
OFFICE 1969 R1W ¼ S 21

Bearing trees OK & tagged.

Douglas Co. Surveyors Office - Larry "Ed" Monrean, Deputy - Randy Smith - Steve Flause - Feb. 14, 1984 - C.S File 62/16-9

-----

Found - 1" IP w/properly mkd. B.C. protruding 12" above ground, in a 2 ft dia. mound of stone.

BTs - Orig. 40", now 48" dia. fir stump w/portion of previously opened blaze badly burned, bears N.2¼°E., 7.9 ft. M70-41 & 1969  
Orig. 30", now 42" diam. fir stump (burned) w/healed blaze bears S.51°W., 30.1 ft. per M70-41. Orig. Rec. & 1969 call S.50°W., 31.0 ft.

New BTs- U.S.F.S. witness sign & post bear N.85°E., 5.8 ft.  
10" dia. fir dbl. blazed & scribed "¼ S16 CS BT" bears N.24½°W. 75.4 ft.  
8" fir, dbl. blazed & scribed "¼ S16 CS BT" bears N.47½°E., 49.3 ft.

Note - No other trees suitable for scribing. Set bearing objects as follows:

B0s - Set 1/2"x8" Bridge Spike in pitch ring of a 50" dia. pine stump. 48" high, stamped "B0 1", set down through a DCSO BT tag, bears S.59°E. 64.5 ft  
Set 1/2"x8" Bridge Spike in pitch ring of a 50" dia. fir stump. Spike stamped "BC 2" set down through DCSO BT tag & bears S.71½°W., 37.1 ft.

Note - Corner lies on a steep SSW slope near East edge of a clear cut, burned & recently replanted.