

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4840)

Set a basalt stone 15x12x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 10" dia., bears N.23°E., 7 lks., mkd: ¼ S4 BT.
A fir, 18" dia., bears S.15°E., 19 lks., mkd: ¼ S9 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Nov. 1969 - C.S. File 54/94-58

Found - No trace of Corner Stone nor NE Bearing Tree.
18", now 24" D.Fir, S.15°E. 12.5 ft. open for scribe "4 S 9". (This tree faces badly, however, by scribe & ring count use for SE BT)
Set - Brass Cap at ¼ cor. mkd: COUNTY SURVEYORS T27S R1W
OFFICE ¼ S 4
1969 S 9
New BT - 24" Cedar N.52°E. 10.0 ft. mkd: ¼ S4 CS BT
Reblazed & Rescribed -
24" D.Fir S.15°E. 12.5 ft. mkd: ¼ S9 CS BT