

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34 only (South)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by S.C. Flint, Contract #473, dated June 5, 1883  
-(DCSO records Vol. 11 Page(s) 4769)

-----  
Set post 48x4 ins. firmly in the ground for stan. cor. to  
secs. 33 & 34 marked S C T27S R1W on N.; S34 on E.; and 33 on  
W. faces, with 3 notches on E. and W. edges, from which  
A Pine 10" dia., bears N.80°E., 24 lks. dist. mkd. T27S  
R1W S34 BT.  
A Fir 42" dia., bears N.50°W., 67 lks. dist. mkd. T27S R1W  
S33 BT.  
A Fir 6" dia., bears S.30°W., 9 lks. dist. mkd. S BT.

GL0 survey by Homer D. Angell, Deputy Surveyor, under  
Contract #746, dated May 5, 1902 - (DCSO records Vol. 11  
Page(s) 4775)

-----  
(76.12 chs.)  
Old sec. cor. on line which I destroy.  
(80.00 chs.)  
Set a Hemlock post 3 ft. long, and 4" sq., 24" in the ground  
for stan. sec. cor. of secs. 33 & 34, marked S C T27S R1W on  
N.; S34 on E.; and S33 on W. faces with 2 grooves on E. and  
4 grooves on W. faces, from which  
A Sugar Pine 40" dia., bears N.40°E., 11 lks. dist. mkd.  
T27S R1W S34 BT.  
A Fir 12" dia., bears N.14½°W., 58 lks. dist. mkd. T27S  
R1W S33 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew -  
Nov. 24, 1969 - C.S. File 54/94

-----  
Found - 40" S.Pine, now down, N.40°E., 7.3 ft., opened for  
scribe.  
12" now 15" Fir, N.14½°W., 38.3 ft., shows good  
scar.  
Set Brass cap at cor. mkd: County Surveyors Office  
T27S R1W S 33 | S 34  
T28S S 4  
1969  
New BT - 18" Hemlock N.43°E., 31.3 ft. mkd. T27S R1W S34 CSBT

Douglas Co. Surveyors Office - Gary L. Langlitz; Peter Earle,  
crew - June 24, 1974 - C.S. File 56/51-23

-----  
Found - Brass cap mkd. as described by DCSO in 1969.  
An approx. 40" Pine stob, bears N.40°E., 7.3 ft., no  
marks visible, area has been disturbed by  
logging. (Cont. Next Page)

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34 only, (South)

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

A 15" D.Fir bears N.14½°W., 38.3 ft., shows good scar.  
No trace of NE. BT, a Hemlock mkd. in 1969.  
New BT - A 24" D.Fir bears N.52°E., 61.2 ft. scribed T27S R1W S34 CS BT.