

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs 27, 28, 33, & 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4821-2)

-----

Set a basalt stone 18x10x8", 14" in the ground for cor. of secs. 27, 28, 33, & 34 mkd with 1 notch on S & 3 notch(es) on E edges, from which

- A fir, 18" dia., bears N.59°E., 33 lks., mkd: T27S R1W S27 BT.
- A fir, 30" dia., bears S.50°E., 17 lks., mkd: T27S R1W S34 BT.
- A hemlock, 20" dia., bears S.75°W., 24 lks., mkd: T27S R1W S33 BT.
- A hemlock, 20" dia., bears N.19°W., 72 lks., mkd: T27S R1W S28 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Dec. 1969 - C.S. File 54/94-101

-----

Found - 18" D.Fir, now 28" N.59°E., 21.8 ft. shows good scar  
30" D.Fir now 36" S.50°E., 11.2 ft., shows good scar.

- 20" Hemlock, now 34" S.75°W., 15.8 ft., scribe visible T27S R1W S33 BT, face rotten.
- 20" Hemlock, now 36" N.19°W., 47.5 ft. face rotten.

Also 18x10x8 stone firmly set at sec. cor. mkd. 1 notch south 3 East.

Set - Brass cap at sec. cor. mkd: COUNTY SURVEYORS T27S R1W  
OFFICE S 28 | S 27  
1969 S 33 | S 34

New BT - 10" Hemlock N.47°W., 33.0 ft. scribed T27S R1W S28 CS BT.

Reblazed & rescribed -  
34" hemlock S.75°W., 15.8 scribed T27S R1W S33 CS BT