

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4823)

Set a basalt stone 20x10x8", 15" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A fir, 18" dia., bears S.60°E., 48 lks., mkd: ¼ S27 BT.
A cedar, 14" dia., bears S.85°W., 12 lks., mkd: ¼ S28 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Dec. 1969 - C.S. File 54/94-82

Found - 20x10x8" stone, mkd: ¼ on west face, firmly in ground.
18" now 27" Fir S.60°E., 31.7 ft. shows good scar.
14" Cedar now 18"S.85°W., 7.9 ft. scribe visible "4" "S" "B"

Set - Brass cap at ¼ cor. mkd: COUNTY SURVEYORS OFFICE
T27S R1W
¼ S 28 | S 27
1969

All BTs OK & tagged.

Douglas Co. Surveyors Office - Randall Smith, Deputy - Stephen Flause - 12/8/1997 - C.S. File 64/78-35

Found - 2½" dia. brass cap on a 1½" o.d. iron pipe protrudes 14" above ground of stone. (1969).
18" now 35" dia. D.Fir, with a fully healed double blaze (note: burnt bark tree is alive), bears S.60°E., 31.7' (agrees with rec.) OBT.
14" now 19" dia. Cedar, with a fully healed single blaze (note: burnt bark, tree is alive), bears S.85°W., 7.9' (agrees with rec.) OBT.

New - 43" dia. D.Fir, barked scribed "¼ S28 CS BT", bears N.37°W., 8.1'.
17" dia. I.Cedar, double blazed and scribed: ¼ S27 CS BT, bears S.5°E., 30.7'.
Corner lies on a steep southerly slope.