

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor. Secs 15, 16, 21, & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4825)

Set a basalt stone 15x12x6", 10" in the ground for cor. of secs. 15, 16, 21, & 22 mkd with 3 notches on S & E edges, from which

- A fir, 28" dia, bears N.16°E. 48 lks. mkd: T27S R1W S15 BT
- A fir, 14" dia. bears S.40°E., 9 lks. mkd: T27S R1W S22 BT
- A fir, 24" dia. bears S.76°W. 42 lks. mkd: T27S R1W S21 BT
- A fir, 12" dia. bears N.71°W. 50 lks. mkd: T27S R1W S16 BT

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Nov. 1969 - C.S. File 54/94-59

Found - No trace of Corner Stone
No trace of NW or SW BTs. due to old skid trail.
28", now 35" D.Fir, N.16°E. 31.7 ft., shows good scar.
14", now 25" D.Fir, S.40°E. 5.9 ft., opened for scribe "S2".

Set - Brass Cap at Cor. mkd: County Surveyors T27S R1W
Office S 16 | S 15
1969 S 21 | S 22

New BT - 26" D.Fir N.61°W., 73.3 ft. mkd: T27S R1W S16 CS BT"
No trees available to SW

This corner lies at NE Cor. very old clear cut unit about 200' North of flat bench, on the point of a small ridge, running SE.

Jim S. Peterson - For: USFS - November 1978 - M 70-41

Found - Doug. Co. Surveyor's Office brass cap extending 18" above ground.
36" Fir, N.18½°E., 31.7 ft. (N.16°E., 48 lks.) Orig
26" Fir, S.40°E., 5.3 ft. (S.40°E., 9 lks.) Orig. BT
26" Fir, N.61¼°W., 71.5 ft. (N.61°W., 73.3 ft.)

New BT - 8" Fir S.63½°W., 25.3 ft. scribed "T27S R1W S21 BT"