

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs 9, 10, 15, & 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4827-8)

-----  
Set a basalt stone 20x12x4", 15" in the ground for cor. of secs. 9, 10, 15, & 16 mkd with 4 notches on S & 3 notch(es) on E edges, from which  
A fir, 12" dia. bears N.75°E. 36 lks. mkd: T27S R1W S10 BT  
A fir, 30" dia. bears S.80°E. 54 lks. mkd: T27S R1W S15 BT  
A fir, 18" dia. bears S.45°W. 58 lks. mkd: T27S R1W S16 BT  
A fir, 12" dia. bears N.50°W., 61 lks. mkd: T27S R1W S9 BT

Douglas Co. Surveyors Office - Frank Jones - W. Penley - Nov. 1969 - C.S. File 54/94-52

-----  
Found - No trace of Corner Stone because this corner lies in logged off unit.  
12", now 14" Fir Stump N.75°E. 23.8 ft., shows good face.  
30" Fir, now 32" Stump, S.80°E. 35.6 ft., shows good face.  
18" Fir, now 22" Stump, S.45°W. 38.5 ft., opened, found scribe.  
12" Fir, now 14" Stump, N.50°E. 40.3 ft., shows good face.  
Set - Brass Cap at Cor. mkd: County Surveyors T27S R1W  
Office S 9 | S 10  
1969 S 16 | S 15  
New BTs- 4" Pine N.57½°W. 78.4 ft. scribed S9 CS BT.  
4" Pine S.82°W. 95.0 ft. scribed S16 CS BT.  
No large trees available for Secs. 9 & 16. This sec. corner lies in cutting unit on steep, south slope  
50" D.Fir N.86½°E. 196.8 ft. mkd: T27S R1W S10 CS BT  
40" D.Fir S.84°E. 213.9 ft. mkd: T27S R1W S15CS BT  
Note - This sec. cor. lies in cutting unit on a steep south slope.