

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4829)

Set a hemlock post, 3 ft. long, 3" sq. 24" in the ground, for 1/4 sec. cor. marked 1/4 S9 on W and 10 on E sides; from which
A fir, 30" dia., bears N.69°E., 35 lks., mkd: 1/4 S10 BT.
A fir, 16" dia., bears N.33°W., 39 lks., mkd: 1/4 S9 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Dec. 1969 - C.S. File 54/94-63

Found - 30" fir, now stump, N.69°E., 23.1 ft. tree cut below face.
16" fir, now stump, N.33°W., 25.7 ft. face badly burnt, fd. "1" above burn area "1/4" very faint on burnt face.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T27S R1W OFFICE 1969 1/4 S 10 | S 9
No trees available to scribe.
Set - 3/4" I.Rod for bearing objects as follows from 1/4 cor:
3/4" IR bears N.20°E., 30.0 ft.
3/4" IR bears S.49°E., 30.0 ft.
3/4" IR's bear S.14°E., 49.4 from each other