

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor Secs 3, 4, 9, & 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4829-30)

-----

Set a basalt stone 15x10x10", 10" in the ground for cor. of secs. 3, 4, 9, & 10 mkd with 5 notches on S & 3 notch(es) on E edges, from which

- A hemlock, 12" dia. bears NE., 47 lks. mkd: T27S R1W S3 BT
- A hemlock, 18" dia., bears S.72°E., 74 lks., mkd: T27S R1W S10 BT.
- A hemlock, 14" dia., bears S.59°W., 62 lks., mkd: T27S R1W S9 BT.
- A hemlock, 24" dia., bears N.49°W., 27 lks., mkd: T27S R1W S4 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Nov. 1969 - C.S. File 54/94-57

-----

Found - Stone, right size but no marks visible of cor. point 14" D.Fir down (Rec. Hemlock), S.59°W. 40.9 ft., scribe visible T27S R1W S9 BT

12", now 10" Hemlock N.45°E. (Rec. NE) 31.0 ft., scribe visible.

18", now 26" Hemlock, S.72°E., 22.4 ft. (Rec. 48.8') scribe visible. "W" "S10 BT"

24" D.Fir (Rec. Hemlock) N.49°W. 17.8 ft., shows good scar.

Set - Using 3 bearings & 3 dist. I set:  
Brass Cap at Cor. Mkd: County Surveyors T27S R1W  
Office S 4 | S 3  
1969 S 9 | S 10

New BT - 14" Hemlock S.38°W. 63.3 ft. mkd: T27S R1W S9 CS BT  
All other Bearing Trees OK and Tagged.