

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4831)

Set a basalt stone 12x10x6", 8" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A fir, 18" dia., bears S.85°E., 23 lks., mkd: ¼ S3 BT.
A fir, 18" dia., bears S.82½°W., 23 lks., mkd: ¼ S4 BT.

Douglas Co. Surveyors Office - M. Lenora Lading - Jim Cook - July 29, 1976 - C.S. File 59/18-10

Found - A 12x10x6" Basalt stone with "¼" on West face.
A 18" now 21" Fir snag bears S.85°E., 15.2 ft with "¼ S3 BT" in cut open blaze.
A 18" now 24" Fir, bears S.81½°W., 27.2 ft. (call S.81½°W., 15.2 ft. Tree is alive with well healed blaze.
Set - A 1x36" IP with brass cap at true corner point, stamped: Douglas Co. Surveyor T27S R1W
1976 ¼ S 4|S 3
Placed orig. stone on West side of cap.
New BT - A 9" Fir, bears N.45°E., 27.9 ft. scribed "¼ S3 CS BT" in double blaze.