

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 4 only, (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4789)

Set a basalt stone 18x12x10 ins., 15" in ground for cor. of secs. 3, 4, 33 and 34, marked with 3 notches on E. and W. edges, from which

- A Fir 18" dia., bears N.31°E., 29 lks. dist. mkd. T26S R1W S34 BT.
- A Fir 18" dia., bears S.61°E., 33 lks. dist. mkd. T27S R1W S3 BT.
- A Fir 18" dia., bears S.6°W., 18 lks. dist. mkd. T26S R1W S4 BT.
- A Fir 18" dia., bears N.31°W., 80 lks. dist. mkd. T26S R1W S33 BT.

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4094 and 4099)

(Page 4094)
The cor. of secs. 3, 4, 33 and 34, which is a basalt stone 5x12x10 ins., above ground, firmly set, marked and witnessed as described by the surveyor general.
(Page 4099)
The old cor. of secs. 3, 4, 33 and 34, which I re-establish as the cor. of secs. 3 and 4 T27S R1W only, by obliterating marks on bearing trees referring to secs. 33 and 34.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 13, 1969 - C.S. File 54/94-42

Found - Corner stone, firmly set, mkd. with 3 notches E-W.
18" now 18" D.Fir S.6°W., 11.9 ft., shows good scar.
18" now 22" D.Fir S.61°E., 21.8 ft., shows good scar

Set Brass cap at cor. mkd: County Surveyors Office
T 26 S R1W S 33
T 27 S 1969 S 4 | S 3

Bearing trees OK and tagged.
Corner lies 89.8 ft. West of sec. cor. 33 & 34, T26-1W.