

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 402700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34 only, T26-1

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4099)

-----  
Set a basalt stone 16x14x6 ins., 11" in the ground for cor. of secs. 33 and 34, marked with 3 notches on E. and W. edges, from which

A Fir 36" dia., bears N.64°E., 35 lks. dist. mkd. T26S R1W S34 BT.

A Fir 16" dia., bears N.51°W., 31 lks. dist. mkd. T26S R1W S33 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 13, 1969 - C.S. File 54/94-41

-----  
Found - Corner stone, firmly in ground, mkd. with notches. 36" now 39" D.Fir N.64°E., 23.1 ft., shows good scar 16" now 22" Fir N.51°W., 20.5 ft. shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office  
T 26 S R1W S 33 S 34  
T 27 S 1969 S 3

Bearing trees OK and tagged.

Corner lies 89.8 ft. East of sec. cor., 3 & 4, T27-1