

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4822)

Set a basalt stone 15x10x8", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A cedar, 12" dia., bears S.43°W., 23 lks., mkd: ¼ S34 BT.
A fir, 8" dia., bears N.71°W., 39 lks., mkd: ¼ S27 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Dec. 1969 - C.S. File 54/94-100

Found - Stone at ¼ cor. Found to be about size but no marks, but we fd. 2 BTs.
12" cedar, now 16", S.43°W., 15.2 ft., shows scribing on open face of "¼ S B"
8" Hemlock (Rec. said to be Fir) now 16" N.71°W., 25.7 ft. shows good axe face.

Set - Brass cap at ¼ cor. by bearing & dist. from both BTs and by approx. cor. stone.

COUNTY SURVEYORS OFFICE

T27S R1W
¼ S 27
S 34

1969

Rescribed - 16" hemlock N.71°W., 25.7 ft. scribed ¼ S27 CS BT

New BT - 10" D.Fir S.6°W., 17.0 ft. scribed "¼ S34 CS BT"

Note - This ¼ cor. lies about 250 ft. south of small creek.

Douglas Co. Surveyors Office - Randall Smith & Stephen Flaese - Dec. 4, 1997 -C.S. 64/78-34

Found - 2½" brass cap on a 1½" O.D. iron pipe protrudes 18" above a mound of stone. 1969

12" now 23" dia. dead, burnt Cedar, with a fully healed single blaze, bears S.43°W., 15.2'. (agrees with rec.) OBT.

8" now 25" dia. dead, burnt Hemlock, with a partially healed burnt blaze, illegible scribing visible, bears N.71°W., 25.7' (agrees w/rec) OBT

10" now 11" dia. dead, burnt D.Fir, with a fully healed single blaze bears S.6°W., 17' (agrees with rec.) 1969

Set - More stone is added to base of monument, BC/IP now protrudes 6" above 2½' dia. mound of stone.

24" dia. D.Fir, double blazed and scribed "¼ S27 CS BT", bears N.79°W., 88.3'.

cont. next pg.

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

31" dia. D.Fir, single blazed and scribed "¼ S34 CS
BT", bears S.24°W., 43.9'.
40" dia. 2' high D.Fir stump, with a PK nail set
through BT tag no top center, bears N.51°E., 4.5'.
Corner lies Approx. 250' south of a creek and 100' north of
a NW running ridge on a steep north slope.