

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4826)

Set a basalt stone 1x10x5", 10" in the ground for 1/4 sec. cor. mkd. 1/4 on N face, from which
A fir, 14" dia., bears S.5°W., 37 lks., mkd: 1/4 S22 BT.
A fir, 30" dia., bears N.20°W., 23 lks., mkd: 1/4 S15 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Dec. 1969 - C.S. File 54/94-99

Found - 30" D.Fir, now burnt stub 50' high, N.20°W., 15.2 ft. opened for scribing "1/4 S15 BT"
14" D.Fir, now burnt stump rotted, S.5°W., 24.4 ft.
Also 15x10x5 stone at 1/4 cor. mkd. "1/4" on North face.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T27S R1W
OFFICE 1/4 S 15
1969 S 22

New BTs- 5" D.Fir N.39°W., 24.5 ft. scribed "1/4 S15 CS BT"
8" D.Fir S.30 1/2°E., 45.2 ft. scribed "1/4 S22 CS BT"

Note - This cor. lies in very brushy clear cut unit.