

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4830)

Set a basalt stone 12x8x6", 8" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 24" dia., bears S.30°E., 35 lks., mkd: ¼ S10 BT.
A fir, 10" dia., bears N.70°W., 35 lks., mkd: ¼ S3 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Nov. 1969 - C.S. File 54/94-33

Found - 12x4x6" stone, firmly set, mkd: "¼" on north face. 24" now 29" Fir, S.30°E., 23.1 ft. shows good scar. No trace of 10" Fir N.70°W., 23.1 ft., find a hemlock at that bearing & dist. but no face.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T27S R1W
OFFICE ¼ S 3
1969 S 10
New BT - 12" Hemlock N.67°W., 23.9 ft. mkd: ¼ S3 CS BT