

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 440700

PRIMARY CORNER DESCRIPTION No. 1/4 cor. for Sec. 3 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4790)

Set basalt stone 20x10x10 ins., 15" in ground for 1/4 sec. cor. marked 1/4 on N. face, from which
A Hemlock 12" dia., bears N.30°E., 5 lks. dist. mkd. 1/4 S34 BT.
A Hemlock 10" dia., bears S.67°E., 14 lks. dist. mkd. 1/4 S3 BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4094 and 4098)

(Page 4094)
The 1/4 sec. cor. which is a basalt stone 6x10x10 ins., above ground, firmly set, marked and witnessed as described by the surveyor general.
(Page 4098)
The old 1/4 sec. cor. which I re-establish as the 1/4 sec. cor. on N. bdy. of sec. 3, T27S R1W only, as follows:
I obliterate marks on N. face of stone and mark 1/4 on S. face, from which
A Hemlock 10" dia., bears S.67°E., 14 lks. dist. mkd. 1/4 S3 BT.
A Fir 10" dia., bears S.57°W., 39 lks. dist. mkd. 1/4 S3 BT.
I obliterate marks on former bearing tree referring to sec. 34.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 13, 1969 - C.S. File 54/94-43

Found - Corner stone, firmly in ground mkd. "1/4" on S. side. 10" now 12" Hemlock S.67°E., 9.2 ft., scribe visible.
10" (?) now 38" D.Fir S.57°W., 25.7 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office
T 26 S
T 27 S R1W 1/4 S 3
1969

Bearing trees OK and tagged.
This corner lies 92.4 ft. West of 1/4 corner sec. 34, T26-1