

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION ¼ Cor Secs 34 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4811)

Set a basalt stone 15x6x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A fir, 12" dia., bears S.72°E., 43 lks., mkd: ¼ S35 BT.
A fir, 40" dia., bears S.30°W., 55 lks., mkd: ¼ S34 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Nov. 1969 - C.S. File 54/94-35

Found - 15x6x6" stone mkd: 1/4
12" now 36" Fir, S.72°E., 28.4 ft. shows faint scar.
40" now 50" Fir, S.30°W., 36.3 ft. shows good scar.
Distances for old faces.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T27S R1W
OFFICE ¼
1969 S 34|S 35

Reblazed & rescribed -
36" D.Fir S.72°E., 28.4 ft. mkd: "¼ S35 CS BT"