

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs 26, 27, 34, & 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4811)

-----

Set a basalt stone 18x12x8", 14" in the ground for cor. of secs. 26, 27, 34, & 35 mkd with 1 notch on S & 2 notches on E edges, from which

- A cedar, 8" dia., bears N.52½°E., 20 lks., mkd: T27S R1W S26 BT.
- A cedar, 12" dia., bears S.32°E., 14 lks., mkd: T27S R1W S35 BT.
- A fir, 16" dia., bears S.33½°W., 42 lks., mkd: T27S R1W S34 BT.
- A cedar, 14" dia., bears N.80°W., 18 lks., mkd: T27S R1W S27 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Nov. 1969 - C.S. File 54/94-36

-----

Found - 18x12x8" stone, firmly set, at section corner.  
14" cedar now stump, N.80°W., 9.5 ft. (rec. 11.9) shows good scar.  
8" cedar now stump, N.52½°E., 13.2 ft. scribe visible "26" and parts of other marks.  
16" D.Fir now stump, S.33½°W., 27.7 ft. shows good scar.  
All trees high stumped.  
12" cedar now stump, S.28°E., 12.9 ft. (rec. S.32°E., 9.2) parts of scribe visible.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T27S R1W  
OFFICE S 27 | S 28  
1969 S 34 | S 35

New BTs- 5" hemlock S.78°E., 51.5 ft. mkd: S35 CS BT  
7" hemlock S.88°W., 55.5 ft. mkd: T27S R1W S34 CS BT  
No other trees available.

This corner on lower side of logging road approx. 150 ft. west, 125 ft. east and 90 ft. north of said road.

U

(Road loops around corner)