TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4813)

Set a basalt stone 12x8x8", 8" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A fir, 16" dia., bears S.32½°E., 19 lks., mkd: ¼ S26 BT.
A fir, 6" dia., bears S.37½°W., 15 lks., mkd: ¼ S27 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Dec. 1969 - C.S. File 54/94-69

Found - 12x8x8 stone, firmly set, mkd: "¼" on west face.
16" now 26" D.Fir, S.32½°E., 12.9 ft., shows good scar.
6" D.Fir, now dead, S.37½°W., 9.9 ft. opened for scribe "¼ S" "T"
Set - Brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1969 T27S R1W ¼ S 27|S 26
New BT - 8" D.Fir S.39°W., 25.4 ft. mkd: "¼ S27 CS BT"