

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs 22, 23, 26, & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4813)

Set a basalt stone 15x12x10", 10" in the ground for cor. of secs. 22, 23, 26, & 27 mkd with 2 notches on S & E edges, from which
A fir, 12" dia. bears N.69°E. 32 lks. mkd: T27S R1W S23 BT
A fir, 30" dia. bears S.40°E. 22 lks. mkd: T27S R1W S26 BT
A fir, 40" dia. bears S.18°W. 52 lks. mkd: T27S R1W S27 BT
A pine, 12" dia. bears N.44°W. 17 lks mkd: T27S R1W S22 BT

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Dec. 1969 - C.S. File 54/94-70

Found - 15x20x10 stone, firmly set, mkd: 2 notches on S & E sides.
12" now 19" D.Fir N.69°E., 21.1 ft., shows good scar.
12" now 19" Pine, N.44°W., 11.2 ft. shows good scar.
40" D.Fir now down, all rotted, S.18°W., 34.3 ft.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T27S R1W
OFFICE S 22 | S 23
1969 S 27 | S 26
New BTs- 14" Pine S.24°E., 35.2 ft. mkd: T27S R1W S26 CS BT
13" D.Fir S.52½°W., 12.0 ft. mkd: T27S R1W S27 CS BT