

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor. Secs 14, 15, 22, & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4815)

Set basalt stone 15x12x6", 10" in the ground for cor. of secs. 14, 15, 22, & 23 mkd with 3 notches on S & 2 notches on E edges, from which

- A fir, 40" dia. bears N.72°E. 44 lks. mkd: T27S R1W S14 BT
- A fir, 40" dia. bears S.64°E. 65 lks. mkd: T27S R1W S23 BT
- A fir, 30" dia. bears S.28°W. 50 lks. mkd: T27S R1W S22 BT
- A yew, 10" dia. bears N.53½°W. 24 lks mkd: T27S R1W S15 BT

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Nov. 1969 - C.S. File 54/94-54

Found - No trace of Corner Stone.
40", now 44" D.Fir, N.72°E. 29.0 ft. shows good scar
40" D.Fir, now stump, S.64°E., 42.9 ft., opened for scribe.
30" D.Fir, now down, S.28°W., 33.0 ft., shows scar.
10" Yew, now down, N.53½°W. 15.8 ft., laying on face.

Set - Brass Cap at Cor. Mkd: COUNTY SURVEYORS T27S R1W
OFFICE S 15 | S 14
S 22 | S 23

New BTs- 4" Maple S.66°E. 31.0 ft. mkd: T27S R1W S23 CS BT
22" Cedar S.82½°W. 44.8 ft. mkd: T27S R1W S22 CS BT
30" D.Fir N.30°W. 52.3 ft. mkd: T27S R1W S15 CS BT