

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4816)

-----

Set a basalt stone 12x12x12", 8" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

- A fir, 12" dia., bears S.79°E., 66 lks., mkd: ¼ S14 BT.
- A fir, 14" dia., bears S.75°W., 15 lks., mkd: ¼ S15 BT.

-----

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Nov. 1969 - C.S. File 54/94-53

-----

Found - No trace of Corner Stone.

- 12" D.Fir, now snag, S.79°E. 43.6 ft., opened for scribe.
- 14" D.Fir, now down, S.75°W. 9.9 ft., opened for definite scribe marks.

Set - Brass Cap at Cor. mkd: COUNTY SURVEYORS T27S R1W OFFICE, 1969 ¼ S 15|S 14

New BTs- 14" D.Fir N.20°E. 32.8 ft. mkd: ¼ S14 CS BT

11" Maple S.51°W. 44.8 ft. mkd: ¼ S15 CS BT