

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias	Description

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4817)

-----  
Set a basalt stone 12x10x6", 8" in the ground for cor. of secs. 10, 11, 14, & 15 mkd with 4 notches on S & 2 notches on E edges, from which  
A fir, 10" dia. bears N.51°E. 52 lks. mkd: T27S R1W S11 BT  
A fir, 10" dia. bears S.51°E. 52 lks. mkd: T27S R1W S14 BT  
A fir, 30" dia. bears S.29°W. 67 lks. mkd: T27S R1W S15 BT  
A fir, 24" dia. bears N.70°W. 46 lks. mkd: T27S R1W S10 BT

Dennis Gaylord USFS & Deputy Co. Surveyor - Witness: William Pack - June 14, 1978 - C.S. 60/11-15

-----  
Found - Orig. corner stone set solidly in place. Stone is soft and no marks remain.  
Orig. 30" Fir is now a windthrow. Stump hole bears S.34°W., 44.2 ft Open & find scribing "T27S".  
Orig. 24" Fir is now a windthrow. Stump hole bears N.64°W., 30.4 ft is lying on face.  
Both BTs to the east are gone.  
Set - Moving the corner stone aside, I SET in it's place a 2 ½" brass cap on a 1" Iron pipe stamped County Surveyors Office T27S R1W S10 S11 S15 S14 1978.  
I bury corner stone alongside brass cap  
New BTs- A 19" G.Fir bears S.8°30'W., 51.6 ft. scribed "T27S R1W S15 CS BT" on a double blaze.  
No suitable trees in Sec. 11.  
A 14" Hemlock bears N.14°W., 48.6 ft. scribed "T27S R1W S10 CS BT" on a double blaze.  
A 8" Grand Fir bears N.47°30'W., 24.7 ft. scribed "T27S R1W S10 CS BT" on a double blaze.  
A 23" D.Fir bears S.27°30'E., 21.3 ft. scribed "T27S R1W S14 CS BT" on a double blaze.