

PRIMARY CORNER DESCRIPTION WC 1/4 Cor. Secs. 10 & 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4818-9)

-----  
N.0°2'W. bet. secs. 10 & 11  
36.15 chs. Impassable cliff... to get over cliff I offset as follows:  
East 50 lks.  
N.0°2'W., 5.25 chs.  
West 50 lks. to point on line bet. 10 & 11  
41.40 chs North side of impassable cliff on line.  
Set a basalt stone, 20x15x5", 15" in the ground for witness corner to ¼ sec. cor. mkd. WC ¼ on W face, from which  
    A fir, 20" dia., bears N.85°E., 66 lks., mkd: WC ¼ S11 BT.  
    A fir, 10" dia., bears S.51°W., 39 lks., mkd: WC¼ S10 BT.  
80.00 chs ... sec. cor. 2, 3, 10, & 11

Douglas Co. Surveyors Office - Gregory E. Quibell, Deputy -  
Debbie Stewart - Sept. 14, 1981 - C.S. File 61/27-40

-----  
Found - Possible orig. stone, 19x15x5". Stone is triangular in shape, with highest point up. Stone is surrounded by a mound of stones. No marks are visible on West face as called for, from which  
    30" stump (orig. 20" Fir) with visible " 4 S11" in opened blaze bears N.85°E., 43.6 ft.  
    15" stump (orig. 10" Fir) with visible " 4 S10 BT" in opened blaze, bears S.51°W., 26.3 ft. (Rec. 25.7 ft.).  
Set - Due to the ground being solid rock, I do not set another monument, but leave 19"x15"x5" triangular stone in its place, surrounded by mound of stone.  
New BTs- 17" Fir bark scribed "WC ¼ S11 CS BT" in double blaze, bears N.11°E., 46.8 ft.  
          10" Fir bark scribed "WC 1/4 S10 CS BT" in double blaze, bears N.56°W., 75.4 ft.  
Note - Corner is on top of Taft Mtn., approx S.55°E., 300-350-ft. from triangulation station "TAFT".