

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs 2, 3, 10, & 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4819)

Set a basalt stone 18x12x8", 14" in the ground for cor. of secs. 2, 3, 10, & 11 mkd with 5 notches on S & 2 notches on E edges, from which
A fir, 12" dia. bears N.38°E., 33 lks. mkd: T27S R1W S2 BT
A fir, 12" dia. bears S.61°E. 32 lks. mkd: T27S R1W S11 BT
A fir, 16" dia. bears S.69°W. 28 lks. mkd: T27S R1W S10 BT
A fir, 16" dia. bears N.54°W., 54 lks. mkd: T27S R1W S3 BT

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Nov. 1969 - C.S. File 54/94-15

Found - 12", now 25" Fir, N.38°E. 21.8 ft., face rotted.
12", now 27" Fir, S.61°E. 21.1 ft., scribe visible "R 1".
16" Fir, now stob, S.69°W. 18.5 ft., stob rotted.
16", now 30" Fir, N.54°W. 35 ft. (Rec.35.6), face rotted out.
Set - Brass Cap at Cor. m&d: COUNTY SURVEYORS T27S R1W
OFFICE S 3 | S 2
1969 S 10 | S 11

Reblazed & rescribed -
25" W.Fir N.38°E. 21.8 ft. scribed T27S R1W S2 CS BT
27" W.Fir S.61°E. 21.1 ft scribed T27S R1W S11 CS BT
30" W.Fir N.54°W. 35.0 ft. scribed T27S R1W S3 CS BT
New BT - 18" D.Fir S.37½°W. 6.8 ft. mkd: T27S R1W S10 CS BT

Fd. & used on BLM dependent resurvey by Jasper M. Sams & Donovan C. Harris, Cadastral Surveyors, under Group No. 747, surveyed June/Aug. 1971 - (DCSO records Vol. 35 Page(s) 14573-4)