

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3 only, (North)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4790)

-----  
Set a basalt stone 15x8x8 ins., 10" in ground for cor. of secs. 2, 3, 34 and 35, marked with 2 notches on E. and 4 notches on W. edges, from which  
A Hemlock 12" dia., bears N.36°E., 27 lks. dist. mkd. T26S R1W S35 BT.  
A Hemlock 28" dia., bears S.67°E., 32 lks. dist. mkd. T27S R1W S2 BT.  
A Hemlock 28" dia., bears S.70°W., 37 lks. dist. mkd. T27S R1W S2 BT.  
A Hemlock 28" dia., bears N.82°W., 59 lks. dist. mkd. T26S R1W S34 BT.

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4094 and 4098)

-----  
(Page 4094)  
The cor. of secs. 2, 3, 34 and 35, firmly set, marked and witnessed as described by the surveyor general.  
(Page 4098)  
The old cor., which I re-establish as the cor. of secs. 2 and 3, T27S R1W only, by obliterating marks on bearing trees referring to secs. 34 and 35.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 1969 - C.S. File 54/94-32

-----  
Found - Mound of stone at corner, stone mkd. with notches, not found.  
28" Hemlock, now snag, S.67°E., 21.1 ft. scribe visible.  
28" now 38" Hemlock S.70°W., 24.4 ft. scribe visible.

Set Brass cap at cor. mkd: County Surveyors Office  
T26S R1W S 34  
T27S S 3 | S 2  
1969  
New BT - 40" Hemlock S.62°E., 41.0 ft. mkd. T27S R1W S2 CS BT  
This corner lies 85.0 ft. E. of cor. secs. 34 & 35, T26-1.